

TR _____

444 5 300

www.odabasi.com.tr

SAL KASA TREYLER

FLATBED



ÜST YAPI

- 9.000mm-13.600mm önü düz hatlı, içten 2440mm dıştan 2550 mm genişliğindedir
- Yanlarda 4 veya 5 kapaklıdır
- Kapaklar dıştan bağlantılı olup, yüksekliği 800mm-900mm'dir
- Taban bir sıra sac yada MDF ile kapatılmaktadır
- Tabanda belirli aralıklarla yerleştirilmiş pres baskı "Z"traversler bulunmaktadır.

ŞASE

- St-52 5 mm sacdan imal edilen şasenin etrafı St-52 120×12 mm alt ve üst lama ile çevriliyerek otomatik tozaltı kaynaklı olarak imal edilip mukavemet kazandırılmıştır.
- Bu şaseler burulmaya karşı birbirine traverslerle bağlanarak desteklenmiştir.

DİNGİL

- 3 adet BPW uyumlu 9 veya 12 ton kapasiteli dingil kullanılmaktadır.



UPPER STRUCTURE

- The front side straight lined 9.000- 13.600 mm; it is width internally 2440 mm externally 2550 mm
- On the sides it has 4 or 5 covers.
- Covers are connected externally and their heights are between 800mm-900mm
- The base is covered with a sheet metal or MDF row
- On the base there are "Z" traverse which are press printed and located at regular intervals.

CHASSIS

- Surroundings of the chassis which is manufactured from St-52 5 mm metal sheet is enforced by covering with St-52 120x12 bottom and upper lama manufactured as automatic submerge arc welded.
- This chassis is supported by connecting traverses to each other towards twisting.

AXLE

- 3 pieces axles compatible with BPW which have 9 or 12 tons capacity are used

