

TR _____

444 5 300

www.odabasi.com.tr

SiLOBAS

CEMENT BULK TRAILER



ÜST YAPI

- Hacim 28-52 m³ hacimlerinde isteğe göre imal edilir.
- Uzunluk 9000 mm- 12000 mm
- Genişlik 2550 mm
- Çalışma basıncı 2 BAR
- Test basıncı 2,6 BAR
- Gövde V tipindedir
- Silobas gövdesinde St 37- 4 mm veya Domex 3 mm sac kullanılmaktadır.

KOMPRESÖR

- 3 kafalı, 8 metreküp/dak debili, pistonlu, elektrik motorlu

BOŞALTIM

- Tank 2 bar hava ile doldurulur. Tabana döşeli vibrasyon hortumları yardımıyla alttaki 4 inç küresel vanadan boşaltılır.

BOŞALTIM SÜRESİ

- 1,5 m³/dak (yeterli hava basıncında)

EMNİYET VENTİLİ

- Tank içi basıncı 2 barla sınırlıdır.

DİNGİL

- 3 adet BPW uyumlu 12 ton kapasiteli dingil kullanılmaktadır.

SÜSPANSİYON

- Parabolik çift katlı Z makaslar ve amortisörler

AYAKLAR

- Çift hızlı teleskopik, mekanik taşıma ayakları, 24 Ton taşıma kapasiteli

BOYA

- Şasi ve üst yapı yıkama + kumlama +2+1 kat Akrilik Boya ile boya fırınında boyanmaktadır.
- Boya rengi müşteri isteği doğrultusunda belirlenmektedir

10



UPPER STRUCTURE

- Volume; it is optionally manufactured from 28 to 45 m³ in volumes.
- Length; 9000 mm to 12000 mm
- Width; 2550 mm
- Working pressure 2 BAR
- Testing pressure 2,6 BAR
- The body is a V-type.
- At the body of cement trailer St 37- 4 mm or Domex 3 mm steel sheet is used.

COMPRESSOR

- 3-headed Electric engine which has a flow rate of 8 cubic meters/min, and pistons

DISCHARGE

- The tank is filled with air at 2 bars. It is discharged from 4 inches of valve at the bottom by means of vibration tubes which are installed on the base.

DISCHARGING TIME

- 1, 5 m³/min (at enough air pressure)

SAFETY VALVE

- Inside pressure of the tank is limited to 2 bars.

AXLE

- Three compatible axles which have 12 tons of capacity are used.

SUSPENSION

- Parabolic double deck Z springs and shock absorbers

SUPPORT STANDS

- Dual-speed telescopic type, mechanic carriage stands, 24 tons carriage capacity

PAINT

- Chassis and upper structure are treated with washing + sanding and painted with 2+1 layers of acrylic paint in the paint oven.
- Paint color is determined in accordance with customer request.

